

RTS 430 Series

RTS 430 SERIES FRAMES

Optimum's steel window and doors offer both reliability and versatility. These characteristics are key when designing a project. One major quality associated with our units is their narrow sightlines. Architects have incorporated this attribute in all aspects of building for over a hundred years, and have designed the gracefulness of steel windows into countless applications. The look is not simply distinctive, it is unique. A new feature offered with our RTS 430 is a thermal break; a barrier designed to separate the interior and exterior walls preventing the transfer of energy from entering or escaping.

FEATURES

- Thermally Broken Hot Rolled Steel window sections
- ANSI/AAMA 101-93 HC40
- 1 5/16" exterior frame depth
- EPDM weather-stripping
- Mitered, welded frame and sash construction
- Uniform sight lines
- Glazed with snap In aluminum glazing beads
- 3/4" to 1 3/8" glazing infill
- 1 casement fastener center of sash rail up to 36", 2 casement fasteners thereafter
- Standard Optimum Window colors (refer to OWM color chart)
- Finish on standard colors baked polyester powder coat

OPTIONS

- RAL colors available as option
- Non metallic color matches are optional & available upon request
- Custom hardware
- Limited operation stops
- Steel brake metal and trim
- Screens

STANDARD WARRANTIES

- 10 years on finish
- 1 year on operable parts

LISTINGS

Frame tests performed in accordance with ASTM E283, ASTM E331 & ASTM E330.

This information is intended for general reference only. For current listing details, please call Optimum Window Mfg. Corp.

***Note: Test specimen size**